

# Zakretni pogon sa krilcem

## Seriya CRB\*BW

### CDRB\*BW

- Veličina 10, 20 i 30 mm sa fiksnim kutem zakretanja 90°, 180°, 270° ili kutem zakretanja od 0° do 240° kontinuirano podesivim.
- Precizna izrada bez zazora.
- Jednostavna konstrukcija omogućava dug radni vijek.
- Opcija je izvedba sa dva krilca.



ø 10, 20, 30, 40 mm



ø 50, 63, 80, 100 mm

| kataloška oznaka** | veličina | kut zakretanja | *dozvoljeni zakretni moment (Nm) | max. kinetička energija (mJ) | prigušenje krajnjeg položaja | priključni navoj |      |
|--------------------|----------|----------------|----------------------------------|------------------------------|------------------------------|------------------|------|
| CRB2BW10-90S-S     | 10       | 90°            | 0,11                             | 0,00015                      | elastično                    | M5×0,8           |      |
| CRB2BW10-180S-S    |          | 180°           |                                  |                              |                              |                  |      |
| CRB2BW10-270S-S    |          | 270°           |                                  |                              |                              |                  |      |
| CRB2BW20-90S-S     | 20       | 90°            | 0,7                              | 0,0004                       |                              | M5×0,8           |      |
| CRB2BW20-180S-S    |          | 180°           |                                  |                              |                              |                  |      |
| CRB2BW20-270S-S    |          | 270°           |                                  |                              |                              |                  |      |
| CRB2BW30-90S-S     | 30       | 90°            | 1,8                              | 0,015                        | M5×0,8                       |                  |      |
| CRB2BW30-180S-S    |          | 180°           |                                  |                              |                              |                  |      |
| CRB2BW30-270S-S    |          | 270°           |                                  |                              |                              |                  |      |
| CRB2BW40-90S-S     | 40       | 90°            | 3,8                              | 0,04                         |                              | M5×0,8           |      |
| CRB2BW40-180S-S    |          | 180°           |                                  |                              |                              |                  |      |
| CRB2BW40-270S-S    |          | 270°           |                                  |                              |                              |                  |      |
| CRB1BW50-90S-XF    | 50       | 90°            | 6                                | 0,082                        | elastično                    |                  | G1/8 |
| CRB1BW50-180S-XF   |          | 180°           |                                  |                              |                              |                  |      |
| CRB1BW50-270S-XF   |          | 270°           |                                  |                              |                              |                  |      |
| CRB1BW63-90S-XF    | 63       | 90°            | 11                               | 0,12                         |                              | G1/4             |      |
| CRB1BW63-180S-XF   |          | 180°           |                                  |                              |                              |                  |      |
| CRB1BW63-270S-XF   |          | 270°           |                                  |                              |                              |                  |      |
| CRB1BW80-90S-XF    | 80       | 90°            | 18                               | 0,398                        | G1/4                         |                  |      |
| CRB1BW80-180S-XF   |          | 180°           |                                  |                              |                              |                  |      |
| CRB1BW80-270S-XF   |          | 270°           |                                  |                              |                              |                  |      |
| CRB1BW100-90S-XF   | 100      | 90°            | 35                               | 0,6                          |                              | G1/4             |      |
| CRB1BW100-180S-XF  |          | 180°           |                                  |                              |                              |                  |      |
| CRB1BW100-270S-XF  |          | 270°           |                                  |                              |                              |                  |      |

\* pri 0,5 MPa

\*\* može se isporučiti sa nosačem za davač signala

#### Pribor

| veličina (mm) | nosač za davač signala za CRB2, CRB1 | podesivi graničnik hoda za CRB2 | pribor za nosač i graničnik za CRB2 |
|---------------|--------------------------------------|---------------------------------|-------------------------------------|
| 10            | <b>P611070-1</b>                     | <b>P611070-3</b>                | <b>P211070-10</b>                   |
| 20            | <b>P611060-1</b>                     | <b>P611060-3</b>                | <b>P211060-10</b>                   |
| 30            | <b>P611080-1</b>                     | <b>P611080-3</b>                | <b>P211080-10</b>                   |
| 40            | <b>P612010-1</b>                     | <b>P612010-3</b>                | <b>P212010-10</b>                   |
| 50            | <b>P411020-1</b>                     | –                               | –                                   |
| 63            | <b>P411030-1</b>                     | –                               | –                                   |
| 80            | <b>P411040-1</b>                     | –                               | –                                   |
| 100           | <b>P411050-1</b>                     | –                               | –                                   |

#### Davač signala

|                              |                                     |
|------------------------------|-------------------------------------|
| ø 10 mm                      | <b>D-90L, D-97L, D-S9PL, D-T99L</b> |
| ø 20, 30, 50, 63, 80, 100 mm | <b>D-R731L, D-R732L</b>             |